


T SERIES track light

T series track light adopts the latest technology of cold forging. The lamp body is made of #1070 aluminium ingot by one time forming without secondary process like splicing, riveting and soldering. The cooling effect of radiator is completely same as that of raw aluminum material. Only 3 steps to make an aluminium ingot turn into a lamp:



1, Put an aluminium ingot into hydropress, getting a primary lamp model.



2. Lathe the lamp model, getting a delicate lamp body.





3, Assemble lamp body with other parts.

The excellent heat conductivity determines lamp quality, combined with high performance light source, we can control our lamp's light decay <10% within 30000hrs, <20% within 50000hrs. The cooling effect of cold forging aluminium is 30% higher than that of same size of #6063 profile aluminium and double better than die casting aluminium.

The Thermal conductivity of different aluminum material:

- Cold forging aluminium (#1070): 226.w/m.k,
- Profile aluminium (#6063): 180.w/m.k
- Die casting aluminium (#ADC12): 98.w/m.k



Features:

T02 series is a track light with independent power box design, mainly for meeting different control systems and different driver brand preferences. The size of the independent power box will be slightly different under the different control system, while its photoelectric performance and heat dissipation performance is completely same as T03 and T09


Famous brand drivers optional: PHILIPS, TRIDONIC, OSRAM, etc. They are all with high PF (>0.9), NO flicker, 50000hrs long lifespan. You can also specify other brands as you like, very flexible and convenient.

Supports CCT



You could choose 3 different color temperature via dip switch, and the total power remains the same.

Supports beam angle




Supports beam angle optional function, you could choose 3 different angles via dip switch, and the total power remains the same.

Function	Form	F/H type	Zoomable type(V)	Zoomable and Shapable type(S)
CCT optional via dip switch		✓	✓	✓
Beam angle optional via dip switch		✓	✗	✗
Intelligent control system		DALI ,KNX,2.4G(CCT),1-10V,TRAC,Dimmable		
Light shield		✗	✗	✗
Housing color		Black, white		

Optical parameters: CCT: 2700K, 3000K,4000K,5000K,6000K; CRI>90,R9>50/CRI>97,R9>95


Item No.	Power(W)	Size (mm)	Illumination 3000K CRI>90	Beam angle	N. W.	Input voltage
T9002	45WX2	a=φ95,b=150, c=150,	7600-9000lm	24° 38° 50°	2.4kg	AC200-240V AC100-277V
T7002	35WX2	a=φ85,b=135, c=150,	6000-7200lm	10° 24° 38° 60°	2.0kg	
T5002	25WX2	a=φ75,b=125, c=130,	4400-5200lm	10° 24° 38° 55°	1.6kg	
T3002	15WX2	a=φ65,b=115, c=130,	2400-3200lm	10° 24° 38° 60°	1.2kg	

Supports F/H/H-DIY optical form



Different optical forms can be selected according to actual lighting requirements. High brightness with UGR19-21(F); moderate brightness with UGR12-17 (H); low brightness with UGR <9 (G); and for some special visual angle (like up and down escalators lighting), a moderate brightness anti-glare type (X) is a good solution.

Support zoomable and shapable form (S)



Support zoomable form (V)



Different from common zoomable track light on the market which light loss might be 50-70% loss (eg, it has 3000LM at 60° but may be only 1000LM at 10°), Our new technology for zoomable design can assure the light loss < 10% when adjusting beam angles.

The latest focusing and shaping technology, can freely change the light spot shape, size, sharpness, etc. Its lighting effect is comparable to advertising backlight, commonly used for cultural relics, paper paintings, and other display lighting.